

ZR-RS Mini Click Rain Sensor

FEATURES

Monitor rainfall level and skip watering when rainfall is over the set amount for outdoor use

Adjustable rainfall amount: 1/8", 1/4", 1/2", 3/4", or 1"

(3, 6, 12, 19 or 25mm)

Cable length: 5m or 7m

No battery required.

Easy mounting to any support or structure with bracket



ZR-RS-P
Mini Click Rain Sensor
for controllers



ZR-RS
Mini Click Rain
Sensor for Tap
Timers

ZR-MS Soil Moisture Humidity Sensor

FEATURES

Monitor soil moisture level and skip watering when soil is too wet.

S: approx. 25% moisture rate

M: approx. 45% moisture rate

L: approx. 65% moisture rate

Cable length: 5m or customized

2 x AA alkaline batteries
required (not included)



ZR-MS Soil Moisture Humidity Sensor

ZR-TM

FEATURES

- Programmable manual watering for up to 120 minutes
- Run Time can be set at 1, 3, 5, 10, 15, 20, 30, 60, 90, 120
- Frequency can be set 1, 2, 3, 4, 6, 8, 12, 24, 48, 72 H and Week
- Time Delay feature for easy setting of desired start watering time
- For taps with 26.5 mm(G 3/4") thread
- 2 x AA alkaline batteries required (not included)

ZR-TN



ZT-TM

FEATURES

- Programmable manual watering for up to 120 minutes
- Run Time can be set at 1, 3, 5, 10, 15, 20, 30, 60, 90, 120
- Frequency can be set 1, 2, 3, 4, 6, 8, 12, 24, 48, 72 H and Week
- For taps with 26.5 mm(G 3/4") thread
- 2 x AA alkaline batteries required (not included)



ZT-TN

Accessories Optional



ZR-RS-P Mini
Click Rain Sensor



ZR-MS Soil Moisture
Humidity Sensor

ZR-TB

FEATURES

- Frequency can be set at 1, 2, 3, 4, 6, 8, 12, 24, 48, 72 H, and Week
- Run Time can be set at 1, 3, 5, 10, 15, 20, 30, 60, 90, 120 mins.
- Time Delay feature for easy setting of desired start watering time
- Rain sensor or moisture sensor connection available to skip watering during rainy days or when soil is too wet.
- For taps with 26.5mm (G 3/4") and 33.3mm (G 1") thread
- 2 x AA alkaline batteries required (not included)

FEATURES

- Programmable manual watering for up to 240 minutes
- Watering cycle can be set for when to start watering and How Long can be set from 5 secs to 360 mins
- How Often can be set from 10 secs to 7 days
- Delay feature at 24, 48, 72 hours
- Rain sensor or moisture sensor connection available to skip watering during rainy days or when soil is too wet
- For taps with 26.5mm (G 3/4") and 33.3mm (G 1") thread
- 2 x AA alkaline batteries required (not included)

Accessories - Optional



**ZR-RS Mini Click
Rain Sensor**



**ZR-MS Soil Moisture
Humidity Sensor**

ZR-TD



ZT-TB



ZT-TD

ZR-T-DD



ZR-T-DD



ZR-T-DD2

ZR-T-DD2

FEATURES

- High quality round blue backlit LCD
- Programmable manual watering for up to 240 minutes
- Watering cycle can be set for when to start watering and How Long can be set for 1-240 mins.
- How Often can be set at every 4, 6, 12 H, and 1-15 days
- Eco feature for splitting watering cycle into mini cycles (Every 1-240 min, Delay 1-240 min)
- Delay feature at 24, 48, 72 hours
- Rain sensor or moisture sensor connection available to skip watering during rainy days or when soil is too wet.
- For taps with 26.5mm (G 3/4") and 33.3mm (G 1") thread
- 2 x AA alkaline batteries required (not included)

FEATURES

- High quality round blue backlit LCD
- Programmable manual watering for up to 240 minutes
- Watering cycle can be set for when to start watering and How Long can be set for 1-240 mins.
- How Often can be set at every 4, 6, 12 H, and 1-15 days.
- Eco feature for splitting watering cycle into mini cycles (Every 1-240 min, Delay 1-240 min)
- Delay feature at 24, 48, 72 hours (when dial at RUN, press +)
- Rain sensor or moisture sensor connection available to skip watering during rainy days or when soil is too wet.
- For taps with 26.5mm (G 3/4") and 33.3mm (G 1") thread
- 2 x AA alkaline batteries required (not included)

Accessories - Optional



ZR-RS Mini Click Rain Sensor



ZR-MS Soil Moisture Humidity Sensor

ZR-T-DDS

FEATURES

- Programmable manual watering for up to 240 minutes
- Run Time can be set at 5, 10, 15...55sec or 1-360min.
- Frequency can be set at 10, 30sec or 1, 3, 5min or 1, 2, 4, 12h or 1-7 days
- Rain Delay settings available at 24, 48 or 72H
- Rain sensor or moisture sensor connection available to skip watering during rainy days or when soil is too wet.
- Pressure rating 0.5 -8.0 Bar
- Flow up to 2.5 Cu. M/Hr.
- CE approved.
- Warranty 2 - years
- For taps with 26.5mm (G 3/4") thread
- 2 x AA alkaline batteries required (not included)

FEATURES

- Programmable manual watering for up to 360 minutes
- Watering cycle can be set for when to start watering and How Long can be set for 10, 15, 20, 30, 40, 45, 50, 55 sec, or 1-360 minutes.
- How Often can be set at every 30 sec or 1, 3, 5 minutes or 1, 2, 3, 4, 5, 6, 7 days
- Delay feature at 24, 48, 72 hours (when dial at RUN, press +)
- Rain sensor or moisture sensor connection available to skip watering during rainy days or when soil is too wet.
- Pressure rating 0.5 -8.0 Bar
- Flow up to 2.5 Cu. M/Hr.
- CE approved.
- Warranty 2 - years
- For taps with 26.5mm (G 3/4") and 33.3mm(G 1") thread
- 2 x AA alkaline batteries required (not included)

Accessories - Optional



ZR-RS Mini Click Rain Sensor



ZR-MS Soil Moisture Humidity Sensor

ZR-T-DDS2



ZR-T-DDS



ZR-T-DDS2