

## Technical Specifications

### VS SPRAY SERIES

---

#### FEATURES

- 2-Year Trade Warranty
- Body cap designed for slip free gripping
- One piece designed wiper seal
- Ultra-low flushing enables 5 PSI sealing
- Two-piece ratchet teeth ensures nozzle alignment 100%  
Virgin material used
- Reinforced ribbed body
- Compatible with all industry-standard female thread nozzles
- Nozzle Options: SVAN-10, SVAN-12, SVAN-15 & SVAN-17

#### OPERATING DATA

- Pressure range: 15 - 70 PSI (1,0 - 4,8 BARS)
- Flow-by: Zero @ 5 PSI (0,3) or greater

Dimensions ½" Female Threaded inlets		
Model	Pop-Up Height	
VS2	2"	5.0 cm
VS4	4"	10.0 cm
VS6	6"	15.0 cm
Exposed Cover	2 ¼"	5,7 cm



VS-4

# VALTICINO

## **Technical Specifications** **VS SPRAY SERIES**

---

LAWN SPRAY HEAD shall be a 2,4 or 6 as manufactured by VALTICINO, or approved equal. Heads shall pop up not less than 2, 4, 12 inches with spring retraction. Heads shall accept a plastic matched precipitation rate nozzle or an adjustable plastic nozzle. Heads shall have ratcheted flow tube for arc location purposes and shall be check valve adaptable.

**CONSTRUCTION:** Body, cover and flow tube shall be high-impact ABS. A double strength stainless steel retraction spring with reversible design shall provide retraction force. Outside entry of sand and dirt shall be prevented with a pressure-activated wiper seal that provides for zero flow by at 5 psi or greater. The cap to body seal shall be pressure activated to prevent loose cap leaks and seal against the inside edge of the body. Arc location shall be by means of a positive stop-ratcheting device permitting the

arc to be located by ratcheting the flow tube while sprinkler is in operation. No tools are required to ratchet the flow tube.

**OPERATION:** The nozzles shall either provide adjustable flows and areas of coverage at rated pressure requirements in both full-circle and part-circle types or shall be fixed arc in both full and part circle types. All nozzles series must have matched precipitation to the extent that full and part circle nozzles can be valved together.

**WARRANTY:** The VS spray head shall have a manufacturer's limited warranty of not less than two (2) years.