

# VALTICINO

## Technical Specifications

### ZR-I-AC ZR-I-DC CONTROLLER

---

#### FEATURES

- 4, 6, and 8 zone model (Indoor rated)
- Outdoor transformer with commercial terminal block, On/Off power switch and LED status indicator
- Large back-lit LCD display
- 2 programs: 1 & 2, Programs can operate stacked
- 4 start times per program
- Zone run times settable from 1 min. to 240 mins., 1-32 days or any day or days of the week, or odd/even days
- Pump(M) and Sensor(R) connection
- AC Model  
Input: AC 230V 50Hz, 150 mA  
Output: AC 24V, 0.8A
- DC Model  
Input: DC 3V  
Output: DC 15V
- 2 x AA alkaline batteries required (not included)



**ZR-I-AC Smart Irrigation Controller**  
**AC - Indoor**  
4, 6, 8 Stations

**ZR-I-DC Smart Irrigation Controller**  
**DC - Indoor**  
4, 6, 8 Stations

# VALTICINO

## *Technical Specifications*

### **ZR-I-AC ZR-I-DC CONTROLLER**

---

CONTROLLER(S) shall be model ZR-I-AC /DC 4,6 & 8 zones as manufactured by VALTICINO. Controller(s) shall be a two (2) program controller

OPERATION: Each program shall have four independent start times, calendar schedules, watering budgets.

Controller shall have a pump start/ master valve position which shall be programmable by zone to operate on demand from any selected zone. Controller shall have input for rain sensor devices. Use of the optional ZR-RS Rain Sensor shall incorporate the rain shutdown function .

Display shall be backlit for clear viewing in all lighting conditions. Zone timing shall be settable from 1 minute to 240 minutes.

All programs shall have the ability to operate in a stacked sequence with independent start time operation.

Program schedules shall include options for days of the week, or an interval of 1 to 30 days.

Manual operation shall be provided by program, by station, or on a programmable test program with durations from ten (10) seconds to ten (10) minutes. The programmable test program shall also check for short and open conditions on each zone each time it is run.

WARRANTY: The ZR-I-AC/DC Series controller shall have a manufacturer's limited warranty of (2) two years.